# **ALPINE SHALLOW 2IN**

# **A1RC-D56** Square Downlight Trim







Fixture Type:

Catalog Number:

Project:

Location:

#### **FINISHES**









Haze

White

Black

**Brushed Nickel** 

Model	Beam	Color Temp	CRI	Lumens	CBCP	Finish
A1RC-D56 (Square)	S 17*	<b>27</b> 2700K <b>30</b> 3000K	90	1025 1065	5000 5185	HZ Haze WT White BK Black BN Brushed Nickel
	<b>N</b> 24°	<b>27</b> 2700K <b>30</b> 3000K	90 90	1025 1065	3215 3334	HZ Haze WT White BK Black BN Brushed Nickel
	<b>F</b> 40°	<b>27</b> 2700K <b>30</b> 3000K	90 90	1005 1045	1769 1835	HZ Haze WT White BK Black BN Brushed Nickel
	<b>W</b> 50°	<b>27</b> 2700K <b>30</b> 3000K	90	945 980	1155 1198	HZ Haze WT White BK Black BN Brushed Nickel

A1RC-D56\_-\_\_\_

Example: A1RC-D56N-27WT

#### **DESCRIPTION**

Shallow housing that is designed to fit in tight plenum spaces without sacrificing lumen output.

## FEATURES

- · Designed to fit in tight plenum
- · Wet location listed for trims
- 2" trim aperture, 2" housing height
- 35° cut-off angle
- Universal input voltage (120V-277V)
- 5 year WAC Lighting product warranty

## LINE DRAWING



#### **SPECIFICATIONS**

**Construction:** Die-cast aluminum trim with die-cast aluminum heat

sink

**Dimming**: 100% - 5% with 0-10V

100% - 5% with Electronic Low Voltage (ELV)/ TRIAC

**Input**: 120V-277V AC

Power: 15W, power factor 0.98

**Mounting:** Retention clips firmly hold trim to housing.

Finish: Powder coated white, black, enamel coated haze,

electroplated brushed

nickel

Standards: UL & cUL Listed, wet location listed trims, Title 24

JA8-2016 Compliant

Ceiling thickness: 1/2" - 1"

aispire.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

# **ALPINE SHALLOW 2IN**

# A1RC-268 Housing







Fixture Type:	
Catalog Number:	
Project:	
Location:	

### **FINISHES**



Black

Model		Finish
A1RC-268	New Construction IC-rated, Airtight	Black

Example: A1RC-268

#### **LINE DRAWING**

