

# ALPINE SHALLOW 2IN

## A1RC-D57 Square Downlight Trimless



Fixture Type:

Catalog Number:

Project:

Location:

### FINISHES



Haze



White



Black



Brushed Nickel

Model	Beam	Color Temp	CRI	Lumens	CBCP	Finish
A1RC-D57 (Square)	S 17°	27 2700K 30 3000K	90 90	1025 1065	5000 5185	HZ Haze WT White BK Black BN Brushed Nickel
	N 24°	27 2700K 30 3000K	90 90	1025 1065	3215 3334	HZ Haze WT White BK Black BN Brushed Nickel
	F 40°	27 2700K 30 3000K	90 90	1005 1045	1769 1835	HZ Haze WT White BK Black BN Brushed Nickel
	W 50°	27 2700K 30 3000K	90 90	945 980	1155 1198	HZ Haze WT White BK Black BN Brushed Nickel
Example: A1RC-D57N-57WT						


### DESCRIPTION

Shallow housing that is designed to fit in tight plenum spaces without sacrificing lumen output.

### FEATURES

- Designed to fit in tight plenum
- Wet location listed for trims
- 2" trim aperture, 2" housing height
- 35° cut-off angle
- Universal input voltage (120V-277V)
- 5 year WAC Lighting product warranty

### LINE DRAWING



### SPECIFICATIONS

<b>Construction:</b>	Die-cast aluminum trim with die-cast aluminum heat sink
<b>Dimming:</b>	100% - 5% with 0-10V 100% - 5% with Electronic Low Voltage (ELV)/ TRIAC
<b>Input:</b>	120V-277V AC
<b>Power:</b>	15W, power factor 0.98
<b>Mounting:</b>	Retention clips firmly hold trim to housing.
<b>Finish:</b>	Powder coated white, black, enamel coated haze, electroplated brushed nickel
<b>Standards:</b>	UL & cUL Listed, wet location listed trims, Title 24 JA8-2016 Compliant
<b>Ceiling thickness:</b>	1/2" - 1"

aispire.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

ALPINE SHALLOW 2IN

A1RC-268 *Housing*




Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



Black

Model	Finish	
A1RC-268	New Construction IC-rated, Airtight	Black

Example: A1RC-268

LINE DRAWING

