ALPINE SHALLOW 3.5IN

A1RD-446 Remodel Housing IC-Rated - Airtight







Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model

A1RD-446	Remodel IC-Rated, Airtight
Example: A1RD-446	

DESCRIPTION


IC-Rated, Airtight,

For use with A1RD-D46, A1RD-D56 ALPINE SHALLOW 3.5IN series trims.

FEATURES

- Airtight
- · Cutout: 4 5/8"
- · 120 277 VAC Input
- Provided with push-in wire connector for easy installation
- · Accommodates ceiling thickness from 1/2"-1"
- 5 year WAC Lighting product warranty
- Does not accomodate adjustments

LINE DRAWING



SPECIFICATIONS

Construction: Housing and junction box are 20 gauge steel

J-Box: Three knockouts for ease of installation. Rated for

branch wiring.

Driver: Electronic driver, 120 - 277VAC input, 15W output.

Power factor >0.9. Dimming with thermal protection.

Mounting: Three heavy gauge inner retention clips push out

onto ceiling or other mounting surface to firmly hold

housing in place.

Accommodates surfaces from 1/2"-1" thick. 4 5/8"

cutout hole.

Dimming: 0-10V Dimming: 100%-0%

ELV Dimming: 100%-5% (120V only)

Standards: Airtight

ETL & cETL Listed.

COMPATIBLE TRIMS SEE TRIM SPEC SHEETS FOR COMPLETE ORDER NUMBER AND SPECIFICATIONS.

ALPINE SHALLOW 3.5IN

A1RD-D46 Series

Round, IC-Rated

A1RD-D56 Series

Square, IC-Rated

aispire.comPhone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

1