

AURORA

A1RD-D461, A1RD-D561 3.5" Color Changing - Downlight Trim





LINE DRAWING (HOUSING)



aispire.com Phone (800) 526.2588 (800) 526.2585 Fax

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Haze

HOUSING (Sold as complete unit)

New Construction, Airtight Housing

Mounting:

Standards:

Finish:

Shown with open square white trim

Retention clips firmly hold trim to housing

ETL & cETL Wet Location listed

Accommodates Ceiling Thickness of 1/2" - 1 1/2"

Powder coated White and Black; Enamel coated

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

AISPIRE retains the right to modify the design of our products at any time as part of the company's continuous improvement program.





WHAT IS AURORA?

- Gradients of saturated colors from 1 100%
- On board closed loop thermal feedback compensates each color channel for thermally induced variations in optical output due to tuning, dimming or ambient temperatures.
- On board closed loop optical feedback measures the lumen depreciation of each channel and rebalances the color model to ensure color consistency over the 50,000 hour life of the module.

WHY PAINT WITH FULL SPECTRUM LIGHT?


Until recently, all light – sunlight, firelight, candlelight, incandescent light –was full spectrum light. Full spectrum light contains all of the visible colors, and, like sunlight, renders colors naturally. Creating electric sunlight means that we needed to mix multiple colors (also known as channels) to replicate the color, beauty and range of sunlight.

WHAT ARE THE BENEFITS OF TUNABLE COLOR?

The 1650-8000K tunable range, 90+ CRI color quality, LED dimming to 0.1%, <2 SDCM color consistency over life, and access to a wide gamut of colors enable the delivery of different lighting profiles that expertly resolve the multiple lighting objectives in your room.

WHAT ARE THE TWO LIGHTING PROFILES OFFERED?

The tunable color profile features a broad tunable range from 1650K to 8000K. The light tracks the CIE Blackbody locus from 1650 - 4500K and then smoothly transitions to the Daylight Curve to 8000K — emulating natural daylight from sunrise to sunset. The warm-dim halogen profile recreates traditional dimming by emulating a halogen lamp from 3050K at full brightness to 1800K at 0.1%.



DYNAMIC DAYLIGHT

Blackbody to Daylight Curve



The Best Light: Aurora recreates and controls light that emulates the spectral quality of daylight — accesses a rich gamut of pastels and saturated colors to unveil new design frontiers.



LED DIMMING

100% - 0.1%

aispire.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

AISPIRE retains the right to modify the design of our products at any time as part of the company's continuous improvement program.







ARCHITECTURE & LANDSCAPE ILLUMINATION

There are extraordinary opportunities in the outdoor lighting environment for controlled illumination. Especially with the addition of robust control of saturation and hue, designers and owners enjoy a level of precision, before thought impossible. Facades can be painted with the exact color desired, and plant materials can be individually selected and then illuminated. Scenes can be preset, and corporate brand colors can be introduced without gels or filters, which invariably shift over time.

CONTROL COMPATIBILITY

ANALOG - DMX can be used to control Dimming and CCT independently, or program Scenes - in any combination of Dimming, CCT, Saturation, and Hue - and recall them with presets or the WAC iOS App.

IOS - Used in conjunction with Digital or Analog controls, each module can be wirelessly commissioned and then the radio turns off for enhanced security.








0 - 10V

VANTAGE

Bluetooth[®] For Commissioning Only

COLOR CONSISTENCY

For fixture-to-fixture color consistency, the light maintain less than 2 Standard Deviation Color Matching over life. 95% of the general population cannot distinguish any difference in the color of light that is <2 SDCM.




COLOR CONSISTENCY OVER LIFE

Less than 2 SDCM

AURORA SPECTRAL DISTRIBUTION CURVE (SPD)

CRESTRON.





aispire.com Phone (800) 526.2588 (800) 526.2585 Fax

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

AISPIRE retains the right to modify the design of our products at any time as part of the company's continuous improvement program.