

ALPINE

A1RE-D46, A1RE-D47 3.5" Adjustable Downlight



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

FINISHES



Trim (Order Housing Separately)	Model	Beam	Color Temp	Lumens	CBCP	Finish
	A1RE-D46 Round Trim Downlight & Adjustable	Spot 16°	27 2700K 30 3000K	855 4989 920 5364	HZWT Haze/White WT White	
		Narrow Flood 36°	27 2700K 30 3000K	840 1463 905 1574		
		Flood 51°	27 2700K 30 3000K	805 839 865 902		
	A1RE-D47 Round Trimless Downlight & Adjustable	Spot 16°	27 2700K 30 3000K	855 4989 920 5364	HZ Haze WT White	
		Narrow Flood 36°	27 2700K 30 3000K	840 1463 905 1574		
		Flood 51°	27 2700K 30 3000K	805 839 865 902		

A1RE-D4_ -----

Example: A1RE-D46-WT

DESCRIPTION

ALPINE offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

FEATURES

- 3 beam angel options included:
- Narrow flood beam film pre-installed, interchangeable flood beam film supplied, remove film for spot beam
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing:
- Vertical Adjustment 0-30°, Horizontal Adjustment 360°
- Shallow housing under 4" depth
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast Aluminum trim and heat sink
Power:	13.5W
Input:	120-277V, 50/60Hz
Dimming:	100%-1% TRIAC,ELV 100%-5% 0-10V
Light Source:	High output COB LED
Rated Life:	50,000 Hours
Mounting:	Retention clip firmly hold trim to housing Cut Out: 4 1/4" New Construction Housing 3 7/8" Remodel Housing
Finish:	Powder Coated White, enamel-coated haze.
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Wet Location Listed, Title 24 JA8-2019 Compliant, IC, Airtight

aispire.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

ALPINE

A1RE-D46, A1RE-D47 3.5" Adjustable Downlight

Housing (Required) - Order separately from trims	Model	Power	Color Temp
	A1RE-248M IC-Rated Airtight	13.5W	27 2700K 30 3000K
	A1RE-346M Non IC- Rated Airtight	13.5W	27 2700K 30 3000K
	A1RE-347M Non IC- Rated Airtight	13.5W	27 2700K 30 3000K

A1RE-__M-__

Example: **A1RE-248M-27**

FEATURES

- Adjustable LED light engine included with housing:
Vertical Adjustment 0-30°, Horizontal Adjustment 365°
- Trim or trimless with die-cast spackle frame included
- Accepts one optional honeycomb louver or optical lens

GLARE CONTROL ACCESSORIES sold separately

LENS-16	HCL	Honeycomb Louver
----------------	------------	------------------

LENS ACCESSORIES sold separately

LENS-16	AMB	Amber
	RED	Red
	FR	Frosted
	SPR	Spread
	BEL	Beam Elongating