


ALPINE

A1RE-P46, A1RE-P47 3.5" Adjustable Pinhole



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____



White

Trim (Order Housing Separately)	Model	Beam	Color Temp	Lumens	CBCP	Finish
	A1RE-P46 Round Trim Adjustable Pinhole	Spot 16°	927 2700K 930 3000K	720 770	5008 5385	WT White
		Narrow Flood 32°	927 2700K 930 3000K	630 675	1425 1532	
		Flood 44°	927 2700K 930 3000K	580 623	824 886	
	A1RE-P47 Round Trimless Adjustable Pinhole	Spot 16°	927 2700K 930 3000K	720 770	5008 5385	WT White
		Narrow Flood 32°	927 2700K 930 3000K	630 675	1425 1532	
		Flood 44°	927 2700K 930 3000K	580 625	824 886	

A1RE-P4_--

Example: **A1RE-P46-WT**

DESCRIPTION

Alpine offers performance features in a simple but versatile package for residential and commercial applications alike. One housing can be used for downlight, adjustable, pinhole, wall wash trims.

FEATURES

- 3 beam angle options included: For Wall Wash trim optimal optics is light engine with no film installed.
- IC-Rated, Airtight, New Construction
- Adjustable LED light engine included with housing
- Shallow housing under 4" depth
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast aluminum trim and heat sink
Power:	13.5W
Input:	120V-277V 50/60Hz
Dimming:	100% - 1% TRIAC, ELV 100% - 5%, 0-10V
Light Source:	High output COB LED rated life of 50,000 hours.
Mounting:	Retention clips firmly hold trim to housing. Cut Out: 4 1/4" New Construction Housing 3 7/8" Remodel Housing
Finish:	Powder coated white
Ceiling Thickness:	1/2" - 1"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL & cUL, Wet Location listed, Title 24 JA8-2019 Compliant

ALPINE

A1RE-P46, A1RE-P47 3.5" Adjustable Pinhole



Model	Model	Power	Color Temp
	A1RE-248M IC-Rated Airtight	13.5W	27 2700K 30 3000K
<p>Remodel Trim</p>	A1RE-346M Non IC Airtight	13.5W	27 2700K 30 3000K
<p>Remodel Trimless</p>	A1RE-347M Non IC Airtight	13.5W	27 2700K 30 3000K

Example: **A1RE-248M-27**

FEATURES

- Adjustable LED light engine included with housing: Optimal Vertical Adjustment for Wall Wash is 15° indexed position
- Trim or trimless with die-cast spackle frame included.
- Accepts one optional honeycomb louver or optical lens.

GLARE CONTROL ACCESSORIES sold separately

LENS-16	Honeycomb Louver
---------	------------------

LENS ACCESSORIES sold separately

LENS-16	AMB Amber
	RED Red
	FR Frosted
	SPR Spread
	BEL Beam Elongating

aispire.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760