

Atmosphere Basics

A1RL Adjustable 4in



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

FINISHES



White

Model & Size	Beam	Color Temp	CRI	Lumens	CBCP	Finish
A1RL-446	F 45°	CS 2700K 3000K 3500K 4000K 5000K	90	750	1050	WT White

Example: A1RL-446F-CSWT


DESCRIPTION

Shallow profile LED that is designed to fit in in furred down ceilings without sacrificing lumen output. Available in 4" adjustable LED recessed.

FEATURES

- 5CCT Selectable - 2700K, 3000K, 3500K, 4000K, 5000K
- Multiple LED array for uniform illumination
- Rotatable multi-axis gimbal ring
- Driver included
- 5 year warranty

LINE DRAWING



SPECIFICATIONS

Color Temp: 2700K / 3000K / 3500K / 4000K / 5000K

Input: 120 -277 VAC, 50/60Hz

CRI: 90

Dimming: ELV: 100-5%, TRIAC: 100-5%

Rated Life: 50000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling

Standards: ETL, cETL, Title 24 JA8-2016 Compliant, Wet Location Listed

Construction: Steel with frosted TIR lens