Alpine Basics Surface

A1RP Surface 6"







Fixture Type:
Catalog Number:
Project:
Location:

FINISHES



Model & Size	Beam	Color Temp	CRI	Watt	Lumens	Finish
A1RP-346 6*	w Wide	30 <i>3000K</i>	90	15W	950	WT White

Example: A1RP-346W-30WT

DESCRIPTION

Multiple high-powered LEDs illuminate an acrylic diffuser uniformly without socket shadows, which are common in conventional flush mounts. This multi-purpose Wet Location, flush mount can be mounted without a transformer on a ceiling or on a wall in a junction box.

FEATURES

- · Multiple LED array for uniform illumination
- ACLED driverless technology
- 5 year warranty

LINE DRAWING



SPECIFICATIONS

Construction: Die-cast aluminum with white acrylic diffuser

Power: 15W

Input: 120 VAC, 50/60Hz

Dimming: ELV: 100-5%

Light Source: Integrated LED

Lens: Translucent acrylic diffuser

Rated Life: 50000 Hours

Mounting: Install over a 3" or 4" junction box

Finish: Electrostatically Powder Coated White

Operating Temp: $-4^{\circ}F$ to 104 $^{\circ}F$ (-20 $^{\circ}C$ to 40 $^{\circ}C$)

Standards: ETL, cETL, Wet Location Listed,

Title 24 JA8-2016 Compliant, ADA

1