

A1RS-A47LM-DW

ASTRO 2" Shallow - Round Adjustable Trimless (Dim-To-Warm)



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The ASTRO Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- Two-piece die-cast construction, compact size suitable for shallow ceiling plenum
- Light engine mounted on trim with springs for easy replacement
- 0-35° vertical tilting and 365° horizontal rotation
- Center beam alignment retained throughout adjustment range
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input: Universal 120-277V AC 50/60 Hz


Dimming: Electronic Low Voltage (ELV): 100%-1%
TRIAC: 100%-1%
0-10V: 100%-1%

Light Source: High output 3-step Mac Adam Ellipse COB
Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly. Safety cabling standard.
Ceiling cutout: Ø 3 1/2"
Accommodates 1/2" - 1" ceiling thickness

Finish: Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.

Standards: ETL & cETL Damp Location Listed,
Title 24 JA8-2019 Compliant.

	Model	Beam	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
	A1RS-A47LM-DW <i>Round Trimless</i>	F 40° W 55°	855 845	1560 1155	3000K-1800K	90	BK DB HZ WT	<i>Black</i> <i>Dark Bronze</i> <i>Haze</i> <i>White</i>

A1RS-A47LM-DW_---

Example: **A1RS-A47LM-DWBK** (Beam F-40° reflector is pre-installed. Beam W-55° reflector is included.)



Please see next page for housing units (required)

A1RS-A47LM-DW

ASTRO 2" Shallow - Round Adjustable Trimless (Dim-To-Warm)



HOUSING (Required)

New Construction IC Airtight		Model	Power
		A1RS-2471L-DW	15W IC
Remodel Non-IC		Model	Power
		A1RS-3471L-DW	15W Non-IC

A1RS____-

Example: A1RS-2471L-DW

GLARE CONTROL ACCESSORIES

LENS-11-HCM LENS-11P-CRL-BK	Honeycomb Louver Cross Louver
--------------------------------	----------------------------------

LENS ACCESSORIES

LENS-11	AMB RED BLU GRN SPR BEL	Amber Red Blue Green Spread Beam Elongating
---------	--	--