

# A1RS-D56LM-DW

## ASTRO 2" Shallow - Square Downlight Trim (Dim-To-Warm)



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION


The ASTRO Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

### FEATURES

- Two-piece die-cast construction, compact size suitable for shallow ceiling plenum
- Light engine mounted on trim with springs for easy replacement
- 30° shielding angle design for better visual comfort
- Field changeable beam angle with reflectors provided
- Accepts one Lens or glare control accessory
- 5 year product warranty

### SPECIFICATIONS

- Construction:** Durable die-cast aluminum construction
- Input** Universal 120-277V AC 50/60 Hz
- Dimming:** Electronic Low Voltage (ELV): 100%-1%  
TRIAC: 100%-1%  
0-10V: 100%-1%
- Light Source:** High output 3-step Mac Adam Ellipse COB  
Rated life of 50,000 hours at L70
- Mounting:** Heavy gauge retention clips support trim firmly. Safety cabling standard. Ceiling cutout: Ø 3 1/2"  
Accommodates 1/2" - 1" ceiling thickness
- Finish:** Electrostatically powder coated White, Black, Dark Bronze. Enamel coated Haze.
- Standards:** ETL & cETL Wet Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant.

|   | Model                               | Beam           | *Lumens    | *CBCP        | Color Temp  | CRI | Finishes   | Reflector/Trim                              |
|---|-------------------------------------|----------------|------------|--------------|-------------|-----|--|---|
|  | <b>A1RS-D56LM-DW</b><br>Square Trim | F 40°<br>W 55° | 980<br>970 | 1620<br>1205 | 3000K-1800K | 90  | <b>BK</b><br><b>DB</b><br><b>HZWT</b><br><b>WT</b> | Black<br>Dark Bronze<br>Haze/White<br>White |

### A1RS-D56LM-DW\_\_\_

Example: **A1RS-D56LM-DWBK** (Beam F-40° reflector is pre-installed. Beam W-55° reflector is included.)

Please see next page for housing units (required)

A1RS-D56LM-DW

ASTRO 2" Shallow - Square Downlight Trim (Dim-To-Warm)



| HOUSING (Required)              |  | Model         | Power      |
|---------------------------------|--|---------------|------------|
| New Construction<br>IC Airtight |  | A1RS-2661L-DW | 15W IC     |
| Remodel<br>Non-IC               |  | A1RS-3661-DW  | 15W Non-IC |

A1RS-\_\_\_-\_\_\_

Example: A1RS-2661L-DW

GLARE CONTROL ACCESSORIES

|                 |                  |
|-----------------|------------------|
| LENS-11-HCM     | Honeycomb Louver |
| LENS-11P-CRL-BK | Cross Louver     |

LENS ACCESSORIES

|         |  |  |
|---------|--|--|
| LENS-11 | AMB<br>RED<br>BLU<br>GRN<br>SPR<br>BEL | Amber<br>Red<br>Blue<br>Green<br>Spread<br>Beam Elongating |
|---------|--|--|