### A1RS-W46A-DW

### ASTRO 2" - Round Wall Wash Trim (Dim-To-Warm)





Fixture Type:	
ı	
Catalog Number:	
Project:	
Location:	

#### **PRODUCT DESCRIPTION**

The ASTRO 2" Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and 360° horizontal rotation, and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

#### **FEATURES**

- Two-piece die-cast construction
- · Light engine mounted on trim with springs for easy replacement
- · 365° horizontal rotation
- · Designed for even wall illumination both vertically and horizontally
- 5 year product warranty

#### **SPECIFICATIONS**

**Construction:** Durable die-cast aluminum construction

Universal 120-277V AC 50/60 Hz Input

Dimming: Electronic Low Voltage (ELV): 100%-1%

> Triac: 100%-1% 0-10V: 100-1%

**Light Source:** High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim firmly.

> Safety cabling standard. Ceiling cutout: Ø 3 1/2" Accomodates 1/2 "- 1 " ceiling thickness

Electrostatically powder coated White, Black, Dark Finish:

Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed,

Title 24 JA8-2019 Compliant.

	Model	Beam	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
5" - 2¾" -   - 4" -	A1RS-W46A Round Trim	A Asym	710	N/A	<b>DW</b> 3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White

### A1RS-W46A-DW

Example: A1RS-W46A-DWBK

Please see next page for housing units (required)

## A1RS-W46A-DW

# ASTRO 2" - Round Wall Wash Trim (Dim-To-Warm)



HOUSING (Required)		Model	Power	
New Construction IC Airtight	5%"   5%"			
	10" 24"MAX	A1RS-2661-DW	15W IC	
Remodel Non-IC	± 2½" 1 2½" 1 2½"		15W Non-IC	
	<b>1</b>	A1RS-3661-DW		

A1RS-\_\_\_-DW

Example: A1RS-3661-DW