A1RS-W56LA-DW

ASTRO 2" Shallow - Square Wall Wash Trim (Dim-To-Warm)





Fixture Type:
Catalog Number:
Project:
Location:

PRODUCT DESCRIPTION

The Astro Recessed series offers a complete line of high performance LED luminaires that provide outstanding functionality and quality. The series features superlative glare control with 30° shielding, 35° vertical tilting and uniform floor-to-ceiling wall washing. Multiple power level options and a full line of round and square, trimmed and trimless luminaires offer versatile solutions for various lighting applications. Easy to order, install, and service.

FEATURES

- · Two-piece die-cast construction, compact size suitable for shallow ceiling
- · Light engine mounted on trim with springs for easy replacement
- Designed for even wall illumination both vertically and horizontally
- 5 year product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction

Input Universal 120-277V AC 50/60 Hz

Dimming: Electronic Low Voltage (ELV): 100%-1%

> TRIAC: 100%-1% 0-10V: 100%-1%

Light Source: High output 3-step Mac Adam Ellipse COB

Rated life of 50,000 hours at L70

Mounting: Heavy gauge retention clips support trim

firmly. Safety cabling standard.

Ceiling cutout: Ø 3 1/2"

Accomodates 1/2 "- 1 " ceiling thickness

Finish: Electrostatically powder coated White, Black,

Dark Bronze. Enamel coated Haze.

Standards: ETL & cETL Wet Location Listed,

Title 24 JA8-2019 Compliant.

	Model	Beam	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim
35%" 	A1RS-W56LA-DW Square Trim	A Asym	675	N/A	3000K-1800K	90	BK DB HZWT WT	Black Dark Bronze Haze/White White

A1RS-W56LA-DW____

Example: A1RS-W56LA-DWWT

Please see next page for housing units (required)

A1RS-W56LA-DW

ASTRO 2" Shallow - Square Wall Wash Trim (Dim-To-Warm)



HOUSING (Required)		Model	Power
New Construction IC Airtight	1134" ————————————————————————————————————	A1RS-2661L-DW	15WIC
Remodel Non-IC	- 5½"	A1RS-3661-DW	15W Non-IC

A1RS-___-

Example: A1RS-2661L-DW