

STEP LIGHTS

A1W13 Step Light with Photocell



Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

FINISHES



BK



SS



WT

Model	Beam	Color Temp	CRI	Lumens	Finish
A1W13 120 VAC	F 55°	30 3000K	90	20 30 65	BK Black on Aluminum SS Stainless Steel WT White on Aluminum

Example: A1W13-30WT


DESCRIPTION

Rectangular step light designed for safety and energy efficiency in indoor and outdoor applications. Features a photocell to reduce energy consumption as part of a durable lighting solution for patios, decks and walkways.

FEATURES

- Options in die-cast aluminum or 316 marine-grade stainless steel
- Fits into 2" x 4" J-Box with minimum inside dimensions of 3"L x 2"W x 2"H
- No driver needed
- No heat radiation
- Low profile, flush to wall aesthetics with no visible hardware
- Balanced lighting, free of shadows with minimum glare
- Integrated photocell for energy saving
- Driver concealed within the fixture
- 5 Year warranty

LINE DRAWING



SPECIFICATIONS

Construction:	Corrosion resistant aluminum alloy, Stainless Steel
Power:	2W
Input:	120 VAC, 50/60Hz
Light Source:	Integrated LED 3 Step MacAdam Ellipse
Lens:	Tempered Glass
Rated Life:	54000 Hours
Finish:	Enamel Coated White on Aluminum, Stainless Steel, Enamel Coated Bronze on Aluminum, Enamel Coated Brushed Nickel on Aluminum, Enamel Coated Black on Aluminum
Operating Temp:	40°F to 122°F (-40°C to 50°C)
Standards:	ETL, cETL, Wet Location Listed, IP66, ADA