AiSPiRE POWER SUPPLY 60w & 96w REMOTE POWER SUPPLY





Fixture Type:

Catalog Number:

Project:

Location:

FINISHES



Model

A2D30-60	60W 24VDC Class 2 Output Power Supply
A2D30-96	96W 24VDC Class 2 Output Power Supply

DESCRIPTION

This class 2 and class P, UL & cUL listed enclosed electronic power supply is the perfect solution for wiring multiple low voltage fixtures. Class 2 power supply is intrinsically safer power supply because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Enclosure cover is easy to remove. Power supply has knockouts on three sides with clips for line voltage wiring. Secondary wiring for class 2 power supplys do not require conduit sheathed cable or clamp wiring techniques. May be dimmed using a TRIAC or electronic low voltage dimmer.


FEATURES

- Short Circuit, over current, over voltage, over temperature protection
- UL Class 2 Output
- 3 prongs input power cord plug
- Pre-wired output wires ready
- 5 years warranty

SPECIFICATIONS

Construction:	Metal
Input:	120VAC
Output	24VDC
Dimning	ELV/TRIAC
PF	>0.9
THD	<20%
Mounting	Surface Mount
Rated Life	50,000 hours
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL & cUL listed, Damp Location listed, Title 24 Compliant FCC Part 15 Class B Compliant

LINE DRAWING



aispire.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

AISPIRE retains the right to modify the design of our products at any time as part of the company's continuous improvement program. SEPT 2020