

120/277VAC, 600mA (9-23VDC)
Dimmable Remote Power Supply




Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

FINISHES

 Black

Model & Product	L x W x H
A2D60-0600A1	8 7⁄8" x 2" x 1 1⁄2"
Example: A2D60-0600A1	


PRODUCT DESCRIPTION

This class 2, UL & cUL listed enclosed electronic power supply is the perfect solution for wiring low voltage fixtures. Class 2 power supply is intrinsically safer because it is considered safety from a fire initiation standpoint and provides acceptable protection from electric shock. Enclosure cover is easy to remove. Power supply has knockouts for line voltage wiring. Secondary wiring for class 2 power supply do not require conduit sheathed cable or clamp wiring techniques. May be dimmed using phase cut (TRIAC/ELV) or 0-10V dimmer.

FEATURES

- Universal Input 120-277VAC
- ≥ 0.9 pf
- Overload and short circuit protection
- TRIAC/ ELV/0-10V Dimming Control
- 0-10V Dimming curve adjustment
- Class 2 Output
- 5 Year warranty

LINE DRAWING



SPECIFICATIONS

Input:	120-277VAC
Output:	600mA, 9-23VDC
Dimming:	TRIAC/ELV/0-10V: 100-1% 0-10V Minimum Current Source: 25uA 0-10V Maximum Current Sink: 400uA
Rated Life:	50,000 hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed,