

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

FINISHES



White

System	Max Run	Power	Length	Color Temp	Color
A2L10	100+lm/ft	1.2W/ft	15 15 ft spool (includes 2pcs A2L30)	27	2700K
A2L20	200+lm/ft	2.4W/ft	40 40 ft spool (includes 2pcs A2L30)	30	3000K
	(Refer to Max Run table below)		100 100 ft spool (includes 2pcs A2L30)		WT White

Example: A2L20-100-30WT

DESCRIPTION

Flexible, customizable, with a low profile, Basics LED Tape delivers precision and performance with two selectable white color temperatures. Smooth robust illumination deployed from evenly placed LEDs for cove, accent and task lighting application. Cuttable in the field. Closet rated.

FEATURES

- Damp location listed
- Title 24 Compliant
- UL/cUL listed
- Available in convenient spools up to 100ft
- Cut and securely reconnect with ease
- May be cut every 4 inches
- Good color rendering
- Suitable for installation in a clothes closet
- 50,000 hour rated life
- 5 year product warranty

SPECIFICATIONS


Construction:	Flexible Light Strip
LED Diode Density:	6 LEDs per cut, 18 LEDs per ft.
Cutting Interval:	4"
Input:	24VDC
Lumens:	Up to 200 lm/ft
Max Run:	Refer to ordering table
CRI:	90
McAdams Steps:	3
Color Temp:	2700K, 3000K
Rated Life:	50,000 Hours
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL, cUL, Damp Location Listed, Title 24 Compliant,
Max Run:	

Total Length of Lead Wire Between Power Supply to Tape	Max Run Length	
	Basics 100	Basics 200
6FT (Comes Standard with Power Supply)	40ft	40ft
12FT	40ft	40ft
18FT	40ft	28ft
24FT	40ft	20ft
30FT	33ft	17ft
40FT	25ft	13ft

LINEAR ALPINE BASICS

Power Supplies and Accessories

Class 2 Power Supply (Required)

	Input	Output	Dimming	
A2D30-60 A2D30-96 	120VAC	24VDC 60W 24VDC 96W	ELV/TRIAC	>0.9 pf, Overload and short circuit protection, 6" Output lead wires

Accessories

Tape to Tape Connector		A2L30-CL	10 pcs	Clear	Connects Tape Sections
Tape to Tape Corner Connector		A2L35-CL	2 pcs	Clear	Connects Tape Sections
Power to Tape Connector		A2L31-CL	10 pcs	Clear	Connects power feed to tape sections
Flex Y Connector		A2L38-WT	1 pc	White	Connects tape sections and power feed, includes A2L36-WT
Flex X Connector		A2L39-WT	1 pc	White	Connects tape sections and power feed, includes A2L36-WT
Low Voltage Wiring Box		A2L36-WT		White	Neatly house connection for up to 2 wires
Joiner Cable		A2L32-002-WT A2L32-006-WT A2L32-012-WT A2L32-036-WT A2L32-072-WT	2 inches 6 inches 1 foot 3 feet 6 feet	White	Extends distance between tape sections
Extension Cable		A2L33-072-WT A2L33-144-WT A2L33-240-WT A2L33-480-WT	6 feet 12 feet 20 feet 40 feet	White	Extends distance between tape sections and power supply (Includes a A2L36-WT & screw driver)
Plastic Mounting Clip		A2L37-CL	10pcs	Clear	Full Installation on non-flat surfaces