
Asymmetrical Recessed Channel A2L6





Fixture Type:	
Catalog Number:	
Project:	
Location:	

FINISHES



Model	Length	Finish
A2L60 (8 ft linear channel) A2L64 (power feed)	8 ft	WT White

Example: A2L60-8-WT


DESCRIPTION

Compatible products are AISPIRE Linear CCT Tunable, ASPIRE Linear RGBWW

LINE DRAWING

FEATURES

- · Installs within drywall depth
- $\cdot \;\;$ Linear channel can be field cut
- · Accommodates one run of ASPIRE Linear indoor tape
- · Dense foam insert for spackling
- Recommended installation within 15 inches of surface to be illuminated
- Aluminum extrusion powder coated in matte white



3" 23/8" 23/8" 35/6" 27/8" 38/6" 27/8" Min 141/6" Max 241/2"

8 ft linear channel

Includes an end cap and diffuser Can be field cut

A2L64-8-WT

Power Feed

Includes a wiring box, two hanger bars, two five-pin InvisiLED adapters, and two end caps. The end cap may be placed on either side or be removed. Hanger bars may install on any side of the writing box.



A2L60-8-WT

aispire.comPhone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760