


# ATMOSPHERE RPS 3.5IN *Remodel Housing, Non IC-Rated, Airtight*

## A2RD-446-CT



Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

*Model*

<b>A2RD-446-CT</b>	Remodel, Non IC-Rated, Airtight
--------------------	---------------------------------

Example: A2RD-466-CT

### DESCRIPTION

ATMOSPHERE RPS is a next level downlight, with an extreme-low profile that is designed to fit in tight plenum spaces without compromising lumen output or glare control. Choose from round or square, trim or trimless, and an array of finishes. With features such as vertical and horizontal adjustment. ATMOSPHERE RPS is suitable for a wide range of applications including residential, commercial, hospitality and architectural.

### FEATURES

- Non IC-rated, remodel housing. Insulation must be kept at least 3" away from housing.
- For use with A2RD-D46, A2RD-D56 ATMOSPHERE RPS3.5IN series trims.
- AISPIRE remote power supply (RPS) required, sold separately.
- Provided with push-in wire connector for easy installation
- 5 year product warranty

### SPECIFICATIONS

<b>Construction:</b>	Housing and junction box, 20 gauge steel
<b>J-Box:</b>	Three knockouts for ease of installation. Rated for branch wiring.
<b>Input:</b>	Class 2 Low Voltage, DC Power Supply. Refer to trim specification for input requirements.
<b>Power:</b>	13W. Refer to trim specifications for consumption data.
<b>Dimming:</b>	Refer to RPS specification for protocol and compatibility
<b>Remote Power Supply (RPS):</b>	<b>A2D20-BK, A2D40-BK.</b> Reference compatible RPS specification for further requirement.
<b>Mounting:</b>	Retention clips firmly hold trim to housing.
<b>Ceiling Thickness:</b>	1/2" - 1"
<b>Cutout:</b>	4 5/8"
<b>Standards:</b>	UL & cUL Listed, Non IC-Rated, Airtight

### COMPATIBLE TRIMS

See trim spec sheets for complete order number and specifications.

#### ATMOSPHERE RPS3.5IN

<b>A2RD-D46 Series</b> Round, Non IC-Rated	<b>A2RD-D56 Series</b> Square, Non IC-Rated
---	--

aispire.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# AiSPiRE Remote Power Supply (RPS)

## A2D LED DMX Power Unit



Model	# of channels	Finish
A2D20 2 x 75W Class 2 output DMX LED power unit	4	BK Black
A2D40 4 x 75W Class 2 output DMX LED power unit	8	BK Black

Example: A2D20-BK

### FINISHES




Black

### FEATURES


- 75W Max. Output Power (Per DMX Power Unit)
- 250mA-1500mA output current selection
- Class 2 power supply
- Built-in DMX512 interface
- IP20 rating
- UL Damp location listed

### LINE DRAWING

A2D20 - 4 Channel



A2D40 - 8 Channel



### INPUT

<b>Voltage Range:</b>	120VAC
<b>Frequency Range:</b>	50/60Hz
<b>Power Factor:</b>	0.99 @100VAC
<b>THD:</b>	<15% @full load
<b>Current:</b>	0.9A @100VAC
<b>Standby Power Consumption:</b>	<0.5w

### OUTPUT

<b>LED Channels:</b>	APD20-BK: 4 Channels APD40-BK: 8 Channels
<b>Selectable Current:</b>	250mA, 300mA, 350mA, 400mA, 450mA, 500mA, 600mA, 700mA, 800mA, 900mA, 1A, 1.1A, 1.2A, 1.3A, 1.4A, 1.5A
<b>DC Voltage Range:</b>	6-48VDC
<b>Current Tolerance:</b>	± 3%
<b>Rated Power:</b>	72W per channel 75W max (per 2-channel output)

### CONTROL

<b>Control Protocol:</b>	DMX 512-A, DMX 512
<b>Diming Range:</b>	0%-100%
<b>Control Input:</b>	DMX RJ45
<b>Dimming Curve:</b>	Linear/Logarithm (Selectable)

### PROTECTION

**Short Circuit, Over Voltage, Over Temp:** Recovers automatically after fault condition is removed

### ENVIRONMENT

**Ambient Operating Temp:** -4°F - 113°F (-20°C - 45°C)

### SAFETY & EMC

- Safety Standard: UL 2018, Damp Location
- EMC Emission: FCC Part 15 Class B
- Surge Immunity: Line-Line 1 kV

aispire.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760



### What is Human Centric Lighting (HCL)

- Throughout evolution, the human visual system has evolved under the natural light of sun and fire.
- Human-centric lighting by definition encompasses the effects of lighting on the physical and emotional being of people.
- As part of the HCL initiative, there is a drive to develop "natural" sources of lighting. The human species has been conditioned to function in daylight hours by the light of the sun, and after dusk, of the warm glow of fire. Thus, we define natural light sources as those which match the spectral distribution of sunlight and firelight.


### Human Centric Light Spectrum

FEATURES	BENEFITS
Spectrum engineered to closely emulate natural light with reduced short blue wavelength intensity	Full, consistent light spectrum with fewer spectral spikes, the closest match to natural light available
Natural and vivid color rendering	Typical 97 CRI with R1-R15 values ranging from 91 to 99 Excellent TM-30 metrics; Rf ranging from 94-97 and Rg from 98-104
High efficacy human-centric spectra	Greater energy savings, lower utility and environment costs
Affordable spectra optimized for humans	Accelerate adoption of full spectrum natural lighting

### Excellent Color Rendering and TM-30 Metrics

CCT	Rf	Rg	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
2700K	95	103	97	99	94	94	97	98	97	98	99	97	91	98	98	95	98
3000K	95	104	98	99	93	94	97	98	96	96	97	96	92	95	98	95	97
3500K	95	98	98	98	97	98	98	98	98	97	93	97	97	95	98	97	98
4000K	97	100	99	99	97	99	99	99	99	98	94	97	99	96	99	98	98
5000K	97	100	98	99	98	98	98	98	99	96	95	98	98	98	98	98	97
5700K	94	98	98	98	97	95	98	97	96	95	92	97	96	98	98	98	97
6000K	95	98	98	98	97	96	98	98	96	96	93	97	96	98	98	98	97

Note: Typical 85C hot values shown, slight differences may exist






## Spectral Matching to Natural Light

- As close of a spectral match as possible to natural light
- Standard LED light sources spectral distribution (SPD) have larger deviations from the Blackbody Curve (BBC)
- ATMOSPHERE significantly reduces the blue spike and cyan valley to deliver a closer match to natural light

**4000K Spectral Comparison BBC vs LED**



*SPD's of LED light sources at 4000K against the blackbody curve.*

These examples deviate from the natural light that humans have evolved under for millions of years. It is recommended to work within the realm of natural light to avoid tweaking circadian rhythms until the effects on humans are understood.