

# Alpine Micro

## A2RU-4A47, A2RU-4A57 - Round and Square Trimless Adjustable Housing



Fixture Type:

Catalog Number:

Project:

Location:

### PRODUCT DESCRIPTION

Minuscule and mighty, peerless and powerful, the new potent Aether Atomic launches into the light. An engineering recessed marvel for next generation futurists. Sublime and serviceable, it's an icon for the ages. Atomic breaks the mold with robust illumination from a diminutive aperture, for a clean, quiet ceiling.

### FEATURES

- Low profile housing for installation in shallow plenums
- High quality stainless steel spackle frame for long lasting durability
- 0 - 25° vertical tilt and 365° horizontal rotation (requires A2RU-TOOL, sold separately)
- Replaceable LED Light Engine
- Frame-In kit optional for new construction installation
- 5 year warranty

### SPECIFICATIONS

<b>Construction:</b>	Durable die-cast aluminum housing with stainless steel spackle frame
<b>Dimming:</b>	100% - 1% ELV, TRIAC and 0-10V
<b>Input Power:</b>	11W
<b>Light Source:</b>	High output COB LED rated life of 50,000 hours
<b>Mounting:</b>	Remodel - Fastened to aluminum ceiling plate with sheetrock screws. Ceiling cutout: 6 1/2" Dia. New Construction - Fastened to frame-in kit with sheetrock screws. Ceiling cutout: 6" Dia.
<b>Ceiling thickness:</b>	1/2" - 2"
<b>Standards:</b>	ETL & cETL Damp location listed, IC rated Airtight Title 24 JAB Compliant

Housings (Order Trim and Power Supply Separately)

	Model	Power	Color Temp	CRI
	<b>A2RU-4A47</b> <i>Round Trimless</i> <i>IC-Rated, Airtight</i>	11W	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	90
	<b>A2RU-4A57</b> <i>Square Trimless</i> <i>IC-Rated, Airtight</i>	11W	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K	90

### A2RU-\_\_\_\_\_-\_\_\_\_

Example: **A2RU-4A47-27**

Please see next page for housing, power supply and tool units (required)

Replacement Light Engine

**RPL-R1A-MOD-927**  
**RPL-R1A-MOD-930**  
**RPL-R1A-MOD-935**  
**RPL-R1A-MOD-940**

Example: **RPL-R1A-MOD-930**

aispire.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste

100 Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave




Ontario, CA 91761

Frame-In Kit (Optional) - Order separately from housings

	Model	Description
	<b>A2RU-167</b>	Frame-In kit for new construction installations

Example: **A2RU-167**

Remote Power Supply (Required) -  
Order separately from trims and housings


	Model	Input	Output	Max # of fixtures per channel	Dimmable	
	<b>A2D60-0600A1</b>	120V - 277V	1 Channel UL Class 2	1 per Channel	100%-1% ELV, TRIAC, 0-10V	8 3/4" x 2" x 1 3/8"
	<b>A2D60-0600A6</b>	120V - 277V	6 Channels UL Class 2	1 per Channel	100%-1% ELV, TRIAC, 0-10V	10 7/8" x 3 7/8" x 1 3/8"
	<b>A2D20-BK</b>	120V	4 Channels UL Class 2	Up to 2 per Channel	100%-1% DMX 512-A, DMX 512	12 7/16" x 9 1/8" x 2 7/8"
	<b>A2D40-BK</b>	120V	8 Channels UL Class 2	Up to 2 per Channel	100%-1% DMX 512-A, DMX 512	12 7/16" x 14 15/16" x 2 7/8"

Example: **A2D60-0600A6**

Home-run wiring. Recommended maximum distance between power supply and compatible light fixture is shown in below table:

	18 AWG	16 AWG	14 AWG	12 AWG
Maximum distance between power supply and light fixture	100 ft	150 ft	200 ft	250 ft

Accessory (Sold Separately)

	Model	Description
	<b>A2RU-TOOL</b>	Tool for angle adjustment and removal of trim and light engine

Example: **A2RU-TOOL**