

Alpine Micro

A2RU-A47M - Round Adjustable Trimless



PRODUCT DESCRIPTION

Minuscule and mighty, peerless and powerful, the new potent Aether Atomic launches into the light. An engineering recessed marvel for next generation futurists. Sublime and serviceable, it's an icon for the ages. Atomic breaks the mold with robust illumination from a diminutive aperture, for a clean, quiet ceiling.

FEATURES

- Robust lumen output from a small aperture
- 0 - 25° vertical tilt and 365° horizontal rotation (requires A2RU-TOOL, sold separately)
- Field changeable beam angle with reflectors provided
- Low profile housing for installation in shallow plenums
- 5 year warranty

Fixture Type:

Catalog Number:

Project:

Location:

SPECIFICATIONS

Construction:	Injection molded polycarbonate low glare trim
Dimming:	100% - 1% ELV, TRIAC and 0-10V
Input Power:	11W
Light Source:	High output COB LED rated life of 50,000 hours
Finish:	Black, Gold, Haze, White
Ceiling thickness:	1/2" - 2"
Standards:	ETL & cETL Damp location listed, IC rated Airtight Title 24 JA8 Compliant

Trims (Order Housing and Power Supply Separately)	Model	Beam	Color Temp	CRI	Lumens	CBCP	Finishes
	A2RU-A47M Round Adjustable Trimless (F beam reflector pre-installed in housing, N and W beam reflectors included)	N 26°	2700K	90	890	2860	BK GL HZ WT Black Gold Haze White
			3000K		955	3075	
			3500K		1020	3290	
			4000K		1090	3505	
		F 36°	2700K	90	875	2320	
			3000K		940	2490	
			3500K		1005	2665	
			4000K		1075	2840	
		W 55°	2700K	90	745	755	
			3000K		800	815	
			3500K		855	870	
			4000K		910	925	

A2RU-A47M- ____

Example: A2RU-A47M-WT

Please see next page for housing, power supply and tool units (required)

Alpine Micro

A2RU-A47M - Round Adjustable Trimless

Housing (Required) - Order separately from trims

Model	Power	Color Temp	CRI
A2RU-4A47 Round Trimless IC-Rated, Airtight	11W	27 2700K	90
		30 3000K	
		35 3500K	
		40 4000K	

A2RU-4A47-___




Example: **A2RU-4A47-27**

Frame-In Kit (Optional) - Order separately from housings

Model	Description
A2RU-167	Frame-In kit for new construction installations

Example: **A2RU-167**

Remote Power Supply (Required) -
Order separately from trims and housings

	Model	Input	Output	Max # of fixtures per channel	Dimmable	
	A2D60-0600A1	120V - 277V	1 Channel UL Class 2	1 per Channel	100%-1% ELV, TRIAC, 0-10V	8 3/4" x 2" x 1 3/8"
	A2D60-0600A6	120V - 277V	6 Channels UL Class 2	1 per Channel	100%-1% ELV, TRIAC, 0-10V	10 7/8" x 3 7/8" x 1 3/8"
	A2D20-BK	120V	4 Channels UL Class 2	Up to 2 per Channel	100%-1% DMX 512-A, DMX 512	12 7/16" x 9 1/8" x 2 7/8"
	A2D40-BK	120V	8 Channels UL Class 2	Up to 2 per Channel	100%-1% DMX 512-A, DMX 512	12 7/16" x 14 15/16" x 2 7/8"

Example: **A2D60-0600A6**

Home-run wiring. Recommended maximum distance between power supply and compatible light fixture is shown in below table:

	18 AWG	16 AWG	14 AWG	12 AWG
Maximum distance between power supply and light fixture	100 ft	150 ft	200 ft	250 ft

Accessory (Sold Separately)

Model	Description
A2RU-TOOL	Tool for angle adjustment and removal of trim and light engine

Example: **A2RU-TOOL**