


# BERGE RPS

## A2W50-30 12" Wall Sconce 3000K



Fixture Type:

Catalog Number:

Project:

Location:

### FINISHES



PN

Model	Forward Voltage	Max. Drive Current	Max. # of Fixtures	Power	Color Temp	Max Lumens	CRI	Finish
A2W50 (Low Voltage)	24V	350mA	2 per channel	11w	30 3000K	559	90	PN

Example: **A2W50-30PN**

\*AISPIRE RPS Required, Sold Separately

### DESCRIPTION

A simple modern design that features a solid crystal block illuminated from within the frame that creates magnificent sparkles as the bubbles within catch the light.

### FEATURES

- AISPIRE remote power supply (RPS) required, sold separately
- Up & down light
- Clear seedy glass
- 5 year warranty

### SPECIFICATIONS

<b>Construction:</b>	Aluminum hardware with seedy glass diffuser
<b>Input:</b>	Class 2 Low Voltage, DC Power See Fixture Configuration table above.
<b>Remote Power Supplies (RPS):</b>	A2W10-30 Reference compatible RPS specifications for further requirements
<b>Dimming:</b>	Refer to RPS specifications for protocol and compatibility
<b>Light Source:</b>	High output 3 Step MacAdam Ellipse LEDs, 90+ CRI Rated life of 50,000 hours at L70
<b>Finish:</b>	Polished Nickel plating finish
<b>Standards:</b>	ETL & cETL Damp Location Listed
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)